

06-01-00

A.

SKJERVEN
MORRILL
MACPHERSON
FRANKLIN
& FRIEL LLP

Docket No.: M-376 US

May 30, 2000

Box Patent Application
Assistant Commissioner for Patents
Washington, D. C. 20231

Enclosed herewith for filing is a patent application, as follows:

Inventors : Daniel R. Zaharris; Lane W. Lee
Title: Method Of Decrypting Data Stored On A Storage Device Using An Embedded Encryption/Decryption Means

X Return Receipt Postcard
X This Transmittal Letter (in duplicate)
15 Pages Specification (not including claims)
7 Pages Claims
1 Page Abstract
5 Sheets of Drawings
3 Pages Declaration For Patent Application and Power of Attorney
1 Page Recordation Form Cover Sheet (in duplicate)
2 Pages Assignment
2 Pages Verified Statement Claiming Small Entity Status (37 CFR 1.9(f) & 1.27(c))--Small Business Concern

CLAIMS AS FILED (fees computed under 37 CFR §1.9(f))

For	Number Filed		Number Extra		Rate		Basic Fee
Total Claims	25	-20 =	5	x	\$ 9.00	=	\$ 45.00
Independent Claims	4	-3 =	1	x	\$39.00	=	\$ 39.00
<input type="checkbox"/> Fee of _____ for the first filing of one or more multiple dependent claims per application							\$
<input type="checkbox"/> Fee for Request for Extension of Time							\$

Please make the following charges to Deposit Account 19-2386:

- ☒ Total fee for filing the patent application in the amount of \$ 429.00
☒ The Commissioner is hereby authorized to charge any additional fees which may be required, or credit any overpayment to Deposit Account 19-2386.

EXPRESS MAIL LABEL NO:

EL 487744924 US

Respectfully submitted,

Dave E. Steuber
Dave E. Steuber
Attorney for Applicants
Reg. No. 25,557

25 Metro Drive, Suite 700
San Jose, CA 95110
Phone 408 453-9200
Fax 408 453-7979

Austin, TX
Newport Beach, CA
San Francisco, CA

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

Applicants: Daniel R. Zaharris; Lane W. Lee
Assignee: DATAPLAY, INC.
Title: METHOD OF DECRYPTING DATA STORED ON A STORAGE
DEVICE USING AN EMBEDDED ENCRYPTION/DECRYPTION
MEANS
Docket No.: M-8376 US

ASSISTANT COMMISSIONER FOR PATENTS
Washington, D. C. 20231

**VERIFIED STATEMENT CLAIMING SMALL ENTITY STATUS
(37 CFR 1.9(F) & 1.27(C)) -- SMALL BUSINESS CONCERN**

Dear Sir:

I declare that I am an official empowered to act on behalf of the concern identified above as assignee.

Exclusive rights to the above invention as described in

- ☒ the specification filed herewith,
☐ U.S. patent application Serial No. _____ filed.

have been conveyed to and remain with the above concern.

For purposes of paying reduced fees under Section 41 of Title 35 of the United States Code with regard to this invention, I declare that the above concern qualifies as a small business concern as defined in 37 CFR 1.9(d) and 13 CFR 121, and more particularly 13 CFR 121.802, namely, (a) the concern's number of employees, including those of its affiliates, does not exceed 500 persons, and (b) the concern has not assigned, granted, conveyed, or licensed, and is under no obligation to assign, grant, convey, or license, any rights in the invention to any person who made it and could not be classified as an independent inventor under 37 CFR 1.9(c), or to any concern which would not qualify as a nonprofit organization under 37 CFR 1.9(e) or a small business concern under 37 CFR 121.802.

LAW OFFICES OF
SKIFFEREN, MORRELL,
MARTINSON, FRANKLIN
& FRIEL LLP

25 METRO DRIVE
SUITE 700
SAN JOSE, CA 95110
(408) 433-0288
FAX (408) 433-7979

I acknowledge my duty to file, in this application or patent, notification of any change in status resulting in loss of entitlement to small entity status prior to paying, or at the time of paying, the earliest of the issue fee or any maintenance fee due after the date on which status as a small entity is no longer appropriate per 37 CFR 1.28(b).

I declare that all statements made herein of my own knowledge are true, all statements made herein on information and belief are believed to be true, and all statements made herein are made with the knowledge that whoever, in any matter within the jurisdiction of the Patent and Trademark Office, knowingly and willfully falsifies, conceals, or covers up by any trick, scheme, or device a material fact, or makes any false, fictitious or fraudulent statements or representations, or makes or uses any false writing or document knowing the same to contain any false, fictitious or fraudulent statement or entry, shall be subject to the penalties including fine or imprisonment or both as set forth under 18 U.S.C. 1001, and that violations of this paragraph may jeopardize the validity of the application or this document, or the validity or enforceability of any patent, trademark registration, or certificate resulting therefrom.

Signature: ASBUNK Date: 5-3-00

Official's Name: Steve Volk

Official's Title: Chairman & CEO

Concern's Name: DataPlay, Inc.

Concern's Address: 6200 Lookout Road, Boulder, CO 80301

LAW OFFICES OF
SKIDGREN, MORRILL,
JACOBSON, FRANKLIN
& FRIEL LLP

25 METRO DRIVE
SUITE 700
SAN JOSE, CA 95110
(408) 431-9000
FAX (408) 431-7979

METHOD OF DECRYPTING DATA STORED ON A STORAGE DEVICE USING AN
EMBEDDED ENCRYPTION/DECRYPTION MEANS

Daniel R. Zaharris

Lane W. Lee

This application is related to U.S. Patent Application No. [attorney docket number M-8382 US], filed April 3, 2000, entitled "DIGITAL RIGHTS MANAGEMENT WITHIN AN EMBEDDED STORAGE DEVICE" which is assigned to the assignee of this application and is incorporated herein in its entirety by this reference.

BACKGROUNDField of the Invention

The present invention relates generally to methods of decryption and more specifically to a method and apparatus for decrypting data using an encryption/decryption engine that is embedded in a device for reading the data.

Description of Related Art

In order to prevent copying or unauthorized use of data, data stored on storage devices, such as CDs, may be encrypted. In order to decrypt the data, a key or password must be provided. Typically, a key or password is a multibit binary number that, when read into logic circuitry, produces an output which enables encryption circuitry to decrypt data. Some types of encryption circuitry require multiple keys to decrypt data. Several schemes have developed for maintaining such keys and passwords.

In some systems the user must provide a code such as a password or a decryption key in order to access the data stored on the medium. This approach, though it may assist in

certain schemes for avoiding unauthorized copying, typically has other associated disadvantages. The user must provide the key or password each time the user accesses the data stored on the medium. If the key or password is only provided once and then stored by the reading device or host computer to relieve the user from having to provide the key each time the user accesses the data stored on the storage medium, the key for decrypting the protected content becomes coupled to a particular host computer or media reader, such that it is cumbersome or impossible to use the medium in more than one machine. In order to use the medium in a different machine, the user must remember, then enter, the password or decryption key in the second machine when the medium is provided to the second machine.

If the key is lost, the user is limited to using the first machine with the stored key to access the data stored on the storage medium. In such approaches, there is no provision for the medium itself to provide, to a computer or reader, information to decrypt the data stored on the medium. If the host device does not store the key, if the user misplaces or forgets the key, the data stored on the storage medium is lost.

Schemes where the password or the decryption key is stored on the player device or host computer also do not offer adequate protection. A user may be able to obtain the password or decryption key or defeat the protection procedure by analyzing or modifying the player or host computer. Once the password or decryption key is discovered, the user can gain access to any storage medium used in the player or the host computer.

SUMMARY

A method of decrypting data stored on a storage medium and encrypted using multiple keys provides a high level of security by combining internal keys generated by the data storage engine reading the data with medium keys stored on the storage medium.

Internal keys are keys that are generated by hardware or software within the data storage

engine. Medium keys are keys that are stored on a storage medium and retrieved from the storage medium when the storage medium is placed in the data storage engine. The medium keys stored on the storage medium may be encrypted. Encrypted medium keys are decrypted using internal keys. The internal keys are combined with the medium keys to generate combination keys. The combination keys are used to decrypt the data stored on the storage medium. In one embodiment, the encryption and decryption operations use the Data Encryption Standard (DES) algorithm, described in Federal Information Processing Standard Publication (FIPS PUB) 46-3, entitled "Data Encryption Standard," incorporated herein by this reference in its entirety.

10 In one embodiment, a host device for reading the storage medium includes an embedded encryption/decryption engine housed on an application specific integrated circuit (ASIC). In a decryption operation, one or more decryption keys and a block of data to be decrypted are input to the encryption/decryption engine, and decrypted data are output from the encryption/decryption engine. The host device also includes a pseudo random number generator, such as a logical feedback shift register, for generating internal keys. The pseudo random number generator is seeded in such a way that every device with the encryption/decryption engine will generate the same internal keys. In one embodiment, the seed number to the pseudo random number generator is stored flash memory external to the ASIC after the ASIC is manufactured to prevent a user or ASIC manufacturer from determining the seed to the pseudo random number generator by reverse engineering the ASIC.

20 The internal keys are used to decrypt a region on the storage medium known as the disk system area. The disk system area includes a master media key. The master media key is the same for a given run of mastered media. The master media key is used to generate one or more medium keys. The medium keys are then combined with the internal keys to

generate combination keys to decrypt data stored on the storage medium. In one embodiment, the storage medium includes a mastered system area containing premastered data and a writable system area containing data saved by the user.

The medium keys include a mastered system area key, a writable system area key, and a file system information key. The medium keys are combined with internal keys in an exclusive "OR" logic operation (XOR) to form the combination keys. The mastered system area key is XOR'd with an internal key to form a mastered system area exclusive OR (MSA XOR) key. The MSA XOR key and an internal key are used to decrypt the data stored on a mastered file system area on the storage medium. The writable system area key is XOR'd with an internal key to form a writable system area exclusive OR (WSA XOR) key. The WSA XOR key and an internal key are used to decrypt selected data stored on a writable file system area on the storage medium. Newly selected information stored on a writable area are encrypted using the WSA XOR key. In some embodiments, the decryption operations are triple DES with two keys.

The file system information key is XOR'd with one of the internal keys to form a new file system information exclusive OR (FSI XOR) key. In one embodiment, file pointers stored in the mastered file system area are double encrypted, such that when the mastered file system area is decrypted by the MSA XOR key, the file pointers remain encrypted. The FSI XOR key and an internal key are used to decrypt file pointers that connect a directory structure stored in the disk system area and mastered file system area with data stored on the other regions of the storage medium. In one embodiment, these file pointers are decrypted and stored within the ASIC. The file pointers are never exposed to a data bus or data buffer outside the ASIC. Storing the file pointers within the ASIC affords an extra level of security.

BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 illustrates a storage medium and a media player for retrieving data stored on the storage medium.

FIG. 2 illustrates the storage medium of FIG. 1.

FIG. 3 illustrates, in a flowchart, a method of decrypting data stored on the storage

5 medium of FIG. 1.

FIG. 4A illustrates the internal keys of FIG. 3.

FIG. 4B illustrates the medium keys of FIG. 3.

FIG. 4C illustrates the combination keys of FIG. 3, generated from combinations of the internally generated keys and the medium keys.

10 FIG. 5 illustrates, in a flowchart, one embodiment of the method of decrypting data of FIG. 3.

DETAILED DESCRIPTION

FIG. 1 illustrates a media player 10 for retrieving the data stored on medium 11.

15 Media player 10 includes a host 13 and a data storage engine 12. Data storage engine 12 can read data stored on storage medium 11 and write data to storage medium 11. Data storage engine 12 may be connected to host 13, or may be integrated into host 13. For example, host 13 may be a personal computer, and data storage engine 12 may be externally connected to the personal computer. Or, host 13 may be a personal player similar to a CD player. In such
20 an embodiment, data storage engine 12 is integrated into the personal player.

Data storage engine 12 reads encrypted data from medium 11, decrypts the data, then sends the decrypted data to host 13 through data buffer 19. For example, if medium 11 stores music, the data storage engine retrieves the encrypted music from medium 11, decrypts the music, then sends the decrypted music to host 13. The host may be, for example, a player
25 that includes speakers. The host then conveys the data to the user.

Data storage engine 12 includes an application specific integrated circuit (ASIC) 14. The ASIC includes an encryption/decryption engine 16. For simplicity, encryption/decryption engine 16 is referred to as a DES engine encrypting and decrypting data using the Data Encryption Standard (DES), though any encryption/decryption algorithm may be used. Several modes of DES encryption and decryption are available. These modes are described in FIPS PUB 81, entitled "DES Modes of Operation," and incorporated herein in its entirety by this reference. In one embodiment, DES engine 16 supports several modes: single DES in ECB and CBC mode and triple DES in ECB and CBC mode. Single DES requires a single key to encrypt and decrypt and triple DES requires two or three keys to encrypt and decrypt. In some embodiments DES engine 16 decrypts using triple DES with two or three keys. In some embodiments DES engine 16 includes two DES cores, one for performing triple DES decryption and one for performing single DES encryption. In such an embodiment, information read from medium 11 can be decrypted by the triple DES decryption core, then immediately reencrypted by the single DES encryption core using a different key. One embodiment of DES engine 16 is available from Intronic Semiconductor of Ottawa, Canada. DES engine 16 is connected to a microprocessor 18 for performing encryption and decryption operations.

ASIC 14 also includes a logical feedback shift register (LFSR) 15, available from Intronic Semiconductor of Ottawa, Canada. LFSR 15 is a pseudo-random number generator which is used to generate numbers that are used as decryption keys. ASIC 14 communicates with host 13 through a data buffer 19. To use the host, a user loads medium 11 into data storage engine 12. The user then requests that the host retrieve data stored on medium 11. Data storage engine 12 retrieves the requested data from medium 11 decrypts the data in DES engine 16. The data is transferred to data buffer 19, then transferred to host 13 for presentation to the user.

FIG. 2 illustrates one embodiment of storage medium 11 of FIG. 1. An example of storage medium 11 is described in U.S. Patent Application Serial No. [Atty Docket No. M-8378 US] filed on the same day as this application, entitled "FORMAT FOR RECORDING DATA ON A STORAGE DISK," assigned to the assignee of this application, and

5 incorporated herein in its entirety by this reference. Storage medium 11 includes at least three areas, a disk system area 20, a mastered file system area 21, and a mastered system area 22. Disk system area 20 includes information such as storage device format characteristics and layout information of storage medium 11. Disk system area 20 also includes a master media key which is used with other keys to decrypt the information stored on the medium.

10 Storage medium 11 also includes a mastered file system area 21 and a mastered area 22. Mastered file system area 21 stores file system information related to the mastered data stored in mastered area 22. Mastered file system area 21 may store, for example, directory information, file attributes, file size, and other file system information. Mastered area 22 stores the actual data that is of interest to the user. The data stored in mastered area 22 may
15 be, for example, music, video, text, or any other kind of data. The data stored in disk system area 20, mastered file system area 21, and mastered area 22 are provided on storage medium 11 when the storage medium is manufactured.

Storage medium 11 may also include a writable file system area 23 and a writable area 24. Writable area 24 stores data provided by the user. For example, if mastered area 22 includes text, writable area 24 may include notations made by the user to the text. Writable
20 file system area 23 includes file system information for the files stored in writable area 24. In one embodiment, storage medium 11 has only disk system area 20, mastered file system area 21, and mastered area 22.

The data stored in disk system area 20, mastered file system area 21, and mastered
25 area 22 are encrypted. In one embodiment, the data in disk system area 20, mastered file

system area 21, and mastered area 22 are encrypted during the mastering process using triple DES. The data in writable file system area 23 and writable area 24 may also be encrypted. The data in areas 23 and 24 are encrypted by encryption/decryption engine 16 of data storage engine 12 when stored by the user on storage medium 11. In one embodiment, the data stored in writable file system area 23 and writable area 24 are encrypted using single or triple DES.

FIG. 3 illustrates a method of decrypting the data stored on storage medium 11. The method uses three types of keys: internal keys, which are generated by data storage engine 12 by a pseudo random number generator; medium keys, which are stored on storage medium 11; and combination keys, which are generated by combining internal keys and medium keys. In stage 30, one or more internal keys are generated by data storage engine 12. In one embodiment, the internal keys are generated by LFSR 15 (FIG. 1) as described below in reference to FIG. 4A. At least one of the internal keys is used to decrypt disk system area 20 on medium 11 (FIG. 2) in stage 32 of FIG. 3. A master media key is included in the disk system area. The master media key is therefore decrypted in stage 32. One or more medium keys are then generated from the master media key in stage 34. In one embodiment, the medium keys are generated by dividing the master media key into segments, as described below in reference to FIG. 4B.

In stage 36, one or more combination keys are generated by combining the medium keys with the internal keys. In one embodiment, the combination keys are generated by XORing an internal key with a medium key, as described below in reference to FIG. 4C. In stage 38, a portion of the data stored on storage medium 11 is decrypted using at least one of the combination keys.

In one embodiment, the information in mastered file system area 21 can be decrypted using one of the combination keys, but the information in mastered area 22 cannot be

decrypted using the combination keys. In this embodiment, after the information stored in mastered file system area 21 describing the files in mastered area 22 is decrypted, the descriptive information is presented to the user. The user then selects portions of the information stored in mastered area 22 to enable. The user enables the information stored in mastered area 22 by retrieving a separate decryption key for decrypting the selected data in the mastered area, as described in U.S. Patent Application Serial No. [Atty Docket No. M-8382 US].

One of the combination keys is used to encrypt information stored by the user in writable file system area 23 and writable area 24. When a user later requests the files stored in writable area 24, they are decrypted using the same combination key.

FIG. 4A-4C illustrate the keys generated to decrypt the data stored on a storage medium 11 according to one embodiment of the present invention. FIG. 4A illustrates the internal keys, the keys generated by ASIC 14 of FIG. 1. LFSR 15 generates two random number keys, first internal key 41 and second internal key 42. LFSR 15 is a mechanism for generating a sequence of binary bits. A first sequence of bits output from the LFSR are first internal key 41 and a second sequence of bits output from LFSR 15 are second internal key 42. LFSR 15 includes a series of cells that are set by inputting an initialization value or "seed" number containing as many bits as there are cells. In each clock cycle, the contents of the cells are shifted right by one position. The data input in the leftmost cell is the result of a logic operation, often an XOR, performed on a subset of cells in the LFSR. The subset of cells whose contents are used in the logic operation are dictated by feedback logic in the LFSR 15, which is selected when the ASIC 14 is manufactured. The output of LFSR 15 is the same for a given seed number and a given set of feedback logic. First internal key 41 and second internal key 42 can therefore be the same for every data storage engine 12.

In one embodiment, the seed provided to LFSR 15 (FIG. 1) is contained in firmware stored in flash memory 17 external to ASIC 14. The seed is not part of the design of ASIC 14, rather it is stored outside the ASIC after the ASIC has been fabricated. Thus, while the particular feedback logic of LFSR 15 may be discovered by reverse engineering ASIC 14, the seed to LFSR cannot be discovered by reverse engineering ASIC 14. Accordingly, one who reverse engineers ASIC 14 is unable to generate first internal key 41 and second internal key 42. Further, ASIC 14 can be manufactured separately from data storage engine 12 without the risk of an ASIC manufacturer discovering the value of the seed to LFSR 15. Only the manufacturer of data storage engine 12, who stores in flash memory 17 external to ASIC 14 the firmware containing the seed to LFSR 15 in ASIC 14, knows the seed value. The seed to LFSR 15 may be generated by another LFSR. In some embodiments, multiple LFSRs connected in series or parallel generate a seed to LFSR 15.

First internal key 41 and second internal key 42 are then used to decrypt disk system area 20 (FIG. 2), using triple DES with two keys. First internal key 41 and second internal key 42 are generated by LFSR 15, then used by DES engine 16 to decrypt the disk system area 20. Thus, the first and second internal keys never leave ASIC 14. ASIC 14 and data buffer 19 may be encased in protective epoxy which covers the ASIC. Such epoxy protects the ASIC by making it nearly impossible to probe the ASIC to determine the signals inside the ASIC, and therefore the internal keys, because any such probing destroys the ASIC.

Once disk system area 20 is decrypted, the master media key can be retrieved from disk system area 20 (block 44 in FIG. 4B). Master media key 44 is the same for a given run of mastered media. For example, every storage medium storing a particular set of data will have the same master media key. Master media key 44 is then used to generate mastered system area key 45A, writable system area key 45B, and file system information key 45C. In one embodiment, master media key 44 is a 256-bit number and mastered system area key

45A, writable system area key 45B, and file system information key 45C are subsets of master media key 44. The breaking of the master media key into subsets to form the mastered system area key, the writable system area key, and the file system information key is an operation that is programmed into firmware stored in flash memory 17 external to ASIC

14.

FIG. 4C illustrates the combined keys. The combined keys are created by combining the medium keys with the internal keys in an exclusive OR (XOR) operation. Each bit in the medium key is XOR'd with the corresponding bit from an internal key. Thus, in one embodiment where the medium keys and internal keys are 56 bit numbers, the combined key

input to DES engine 16 of FIG. 1 is the output from 56 XOR gates. Mastered system area key 45A is XOR'd with first internal key 41 to form mastered system area exclusive OR (MSA XOR) key 46. Writable system area key 45B is XOR'd with first internal key 41 to form writable system area exclusive OR (WSA XOR) key 47. File system information key 45C is XOR'd with first internal key 41 to form file system information exclusive OR (FSI XOR) key 48.

For clarity, the names of the medium keys are spelled out and the names of the combination keys are abbreviated. Thus, the medium keys are referred to as the mastered system area key, the writable system area key, and the file system information key. The combination keys are referred to as the MSA XOR key, the WSA XOR key, and the FSI XOR key.

Internal keys 41 and 42 are generated by hardware in ASIC 14, e.g. LFSR 15. Medium keys 45A, 45B, and 45C and combined keys 46-48 are generated by firmware operations stored in ASIC 14.

FIG. 5 illustrates a method of decrypting data stored on storage medium 11 using the keys generated in FIG. 4A-4C. In stage 50, the storage medium is inserted into a data storage

engine. ASIC 14 seeds LFSR 15 to form the first and second internal keys of FIG. 4A. The two internal keys are then used to decrypt the data stored in disk system area 20 of FIG. 2, shown in stage 54 of FIG. 5. Once disk system area 20 is decrypted, the master media key is retrieved in stage 56. The master media key is then used to generate the file system information key in stage 57. The user then requests some data from the storage medium. Depending on the data requested by the user, the mastered system area key and/or the writable system area key are generated from the master media key, shown in stages 60 and 63.

In some embodiments, some critical data stored in the disk system area, the mastered file system area, or the writable file system area, are double-encrypted. Such critical data may include file pointers between a directory or file system structure stored in any of these areas and the data stored in the mastered area and/or the writable area. Thus, when the information stored in the disk system area, mastered file system area, or writable system area are decrypted, these file pointers remain encrypted. The file pointers may be double encrypted to provide an extra level of security to the data stored on the storage medium. Once the data stored in the disk system area, the mastered system area, and the writable system area are decrypted and sent to data buffer 15 (FIG. 1), they become more vulnerable to "snooping" than when inside the ASIC, because the data buffer, even if protected by epoxy, is more vulnerable to probing than the protected ASIC. If a user is able to probe the data buffer, the user may be able to transfer the data from storage medium 11 to another medium. Once the data is stored on another medium in an unencrypted form, the data can be duplicated and distributed, thus defeating the encryption scheme. However, if the file pointers connecting the data to the file system structure defining the data are still encrypted, unencrypted data taken from the data buffer may be difficult or impossible to decipher. Thus, the unencrypted file pointers are never exposed to a data buffer outside ASIC 14.

When the user requests a particular file, the encrypted file pointer is retrieved from the data buffer, sent to microprocessor 18 (FIG. 1), and decrypted by DES engine 16. In stage 58, the file system information key generated from the master media key is XOR'd with the first internal key to generate the FSI XOR key. In stage 59, the FSI XOR key and the second internal key are then input to DES engine 16 to decrypt the file pointers within the DES engine using triple DES with two keys. Using the file pointer, the file requested by the user is sent to data buffer 19 to be retrieved by the host. The unencrypted file pointer is stored only in memory inside the ASIC, and therefore never leaves ASIC 14. The unencrypted file pointer is therefore less vulnerable to unauthorized use than data stored on the data buffer.

In stage 61 of FIG. 5, the mastered system area key generated from the master media key is XOR'd with the first internal key generated by the ASIC to form a MSA XOR key. The mastered file system area and/or the mastered area can then be decrypted in stage 62 using two key triple DES with the MSA XOR key and the second internal key as the two keys. Similarly, in stage 64, the writable system area key generated from the master media key is XOR'd with first internal key generated by the ASIC to form a WSA XOR key. The writable file system area and/or the writable area can then be decrypted in stage 65B using two key triple DES with the WSA XOR key and the second internal key as the two keys. In another embodiment, the writable system area is decrypted in stage 65A using the WSA XOR key as the key to single DES decryption. In addition, when the user requests that data be saved to the writable system area, the data is encrypted with single DES using the WSA XOR key before it is written to the writable system area. Though the WSA XOR key may be used to encrypt and decrypt unmastered, user-generated data, the WSA XOR key itself is generated from the master media key, which is mastered.

The keys shown in FIG. 4A are generated in stage 52 of FIG. 5. The keys shown in FIG. 4B are generated in stages 54, 56, 57, 60 and 63 of FIG. 5. The keys shown in FIG. 4C are generated in stages 58, 61, and 64 of FIG. 5.

Since every data storage engine has the same firmware seed to LFSR 15, every data storage engine will generate the same first internal key 41 and second internal key 42 (FIG. 4A). Thus, any data storage engine is able to decrypt and read the data stored in disk system area 20 of storage medium 11. However, any engine or host that is not able to generate first internal key 41 and second internal key 42 cannot decrypt disk system area 20. Such a device will not be able to retrieve any data from storage medium 11 even if the master media key is known, because disk system area 20 stores an encrypted directory structure for the data stored in mastered system area 22 and writable system area 24. If the directory structure is not known, the data stored in the mastered system area and writable system area are difficult to access because the user cannot know where one file ends and another begins. In addition, the mastered file system area and the writable file system area are decrypted using keys generated by combining keys generated from the master media key with keys generated by the data storage engine. Thus, knowing the master media key without the internal keys or the internal keys without the master media key does not allow a user to access the data stored on the storage medium. Further, even if the master media key is known, the mastered system area key, the writable system area key, and the file system information key are not known.

The data stored in the mastered area may be further encrypted during the mastering process. Thus, once stages 60-62 of FIG. 5 are completed, the data stored in the mastered system area may need to be further decrypted using the DES engine, according to a process specified by the producer of the mastered data.

Various modifications and adaptations of the embodiments and implementations described herein are encompassed by the attached claims. For example, any encryption or

decryption algorithm may be used, not just DES. Also, any of the decryption or encryption operations may be single DES in any DES mode, triple DES with two keys in any DES mode, or triple DES with three keys in any DES mode. In addition, new keys may be generated from the internal and medium keys using any combination operation, not just XOR as described herein. Finally, the combined keys are not limited to the combinations of internal keys and medium keys described herein.

CLAIMS

We claim:

1. A method of decrypting data stored on a storage medium using an encryption/decryption core embedded on a data storage engine, the method comprising:
5 generating an internal key using the data storage engine;
 retrieving a medium key stored on the storage medium using the internal key;
 generating a combination key by combining the medium key with the internal
key;
 decrypting a first portion of data stored on the storage medium using said first
10 combination key.
2. The method of Claim 1 wherein the retrieving a medium key stored on the
storage medium further comprises:
 decrypting a master media key
5 generating the medium key from the master media key;
3. The method of Claim 1 wherein the internal key is generated by a pseudo-
random number generator.
- 20 4. The method of Claim 2 wherein the master media key is decrypted using triple
DES for two keys, wherein a first key is a first internal key and a second key is a second
internal key.

5. The method of Claim 2 wherein the master media key is a 256-bit random number and the plurality of medium keys are generated by dividing the master media key into a plurality of 64-bit numbers.

5 6. The method of Claim 1 wherein the combination key is generated by combining the internal key with the medium key in an exclusive OR function.

7. The method of Claim 1 wherein the first portion is decrypted using triple DES for two keys, wherein a first key is the combination key and a second key is an internal key.

10 8. The method of Claim 2 wherein the plurality of medium keys comprises a mastered system area key, a writable system area key, and a file system information key.

15 9. The method of Claim 2 further comprising:
generating an additional internal key.

20 10. The method of Claim 9 wherein:
the plurality of medium keys comprises a mastered system area key;
the first portion of data comprises mastered data;
generating a combination key further comprises combining the mastered
system area key with the internal key in an XOR function; and
decrypting the first portion further comprises using triple DES with two keys,
wherein the first key is the combination key and the second key is the additional
internal key.

11. The method of Claim 9 wherein:

the plurality of medium keys comprises a writable system area key;

the first portion of data comprises unmastered data;

5 generating a first combination key further comprises combining the writable system area key with the internal key in an XOR function; and
decrypting the first portion further comprises using triple DES with two keys, wherein the first key is the combination key and the second key is the additional internal key.

10 12. The method of Claim 11 further comprising:

storing a second portion of data on said unmastered area; and

encrypting the second portion of data using single DES, wherein the key is the combination key.

15 13. The method of Claim 9 wherein the plurality of medium keys comprises a file system information key, the method further comprising:

generating an additional combination key by combining the file system information key with the internal key in an XOR function;

20 decrypting a file system stored on the storage medium;
decrypting a file pointer linking the file system to the first portion of data using triple DES with two keys, wherein the first key is the second combination key and the second key is the additional internal key.

14. A method of decrypting data using a data storage engine comprising a data buffer and an ASIC, the ASIC having an encryption/decryption engine and a pseudo-random number generator, and the data being stored on a storage medium, the method comprising:

generating a plurality of internal keys using the pseudo-random number
5 generator;

decrypting a master media key and a file system structure corresponding to a first portion of the data using at least one internal key;

generating a plurality of medium keys from the master media key;

generating a plurality of combination keys from the plurality of medium keys
10 and the plurality of internal keys;

decrypting a first portion of the data using a first combination key.

15. The method of Claim 14 wherein the pseudo-random number generator comprises a logical feedback shift register, and wherein “generating a plurality of internal
5 keys” further comprises:

seeding the logical feedback shift register with a seed stored in a flash
memory.

16. The method of Claim 14 further comprising:

20 decrypting a plurality of file pointers linking the file system structure to the data using a second combination key, wherein the plurality of decrypted file pointers is stored within the ASIC.

17. The method of Claim 14 wherein said first portion comprises mastered data,
25 the method further comprising:

encrypting a second portion of data, the second portion comprising unmastered data.

18. The method of Claim 17 wherein:

5 said decrypting a first portion of data further comprises decrypting using triple DES with two keys, wherein a first key is the first combination key and the second key is a first internal key; and

said encrypting further comprises encrypting using single DES, wherein the key is a second combination key.

10 19. The method of Claim 14 further comprising

decrypting a second portion of the data using a second combination key, wherein the first portion comprises mastered data and the second portion comprises data saved by a user.

15 20. A method of encrypting data stored on a storage medium using an encryption/decryption core embedded on a data storage engine, the method comprising:

generating a plurality of internal keys using the data storage engine;

20 decrypting a master media key stored on the storage medium using at least one of the plurality of internal keys;

generating a plurality of medium keys from the master media key;

generating a first combination key by combining a medium key with an internal key;

encrypting a portion of unmastered data using said first combination key;

25 storing the portion on the storage medium.

21. The method of Claim 20 wherein encrypting a first portion further comprises encrypting using single DES.

5 22. A method of decrypting data stored on a storage medium using a data storage engine, the method comprising:

decrypting a file system structure corresponding to the data, the file system structure comprising at least one file;

10 decrypting a file pointer, the file pointer indicating a location on the storage medium of a file in the file system structure;

retrieving a portion of the data from the location indicated by the file pointer.

15 23. The method of Claim 22 further comprising decrypting the portion of data stored at the location indicated by the file pointer.

20 24. The method of Claim 22 wherein the data storage engine comprises an application specific integrated circuit and a data buffer, wherein the file pointer is double encrypted, and wherein "decrypting a file pointer" further comprises:

decrypting the double encrypted file pointer, such that the file pointer is single encrypted;

storing the single encrypted file pointer in the data buffer;

retrieving the single encrypted file pointer from the data buffer;

25 decrypting the single encrypted file pointer within the application specific integrated circuit.

25. The method of Claim 24 further comprising:

 sending the portion of data retrieved from the location indicated by the file
pointer to the data buffer.

METHOD OF DECRYPTING DATA STORED ON A STORAGE DEVICE USING AN EMBEDDED ENCRYPTION/DECRYPTION MEANS

Daniel R. Zaharris

Lane W. Lee

5 A method of decrypting data is provided for decrypting data stored on a storage medium using an encryption/decryption means embedded on data storage engine for reading the data from the medium. The data storage engine generates at least a set of internal keys. The internal keys are used to decrypt a master media key stored on the storage medium. The master media key generates a set of medium keys. The medium keys are combined with the
10 internal keys to generate a set of combined keys. The combined keys are used to decrypt portions of the data stored on the storage medium.

10




FIG. 1

The diagram illustrates a disk layout with concentric circles. The innermost circle is labeled "Mastered File System Area 21". The next ring is labeled "Mastered Area 22". The third ring is labeled "File System Area 23". The outermost ring is labeled "Disk System Area 20".

FIG. 2




FIG. 3




FIG. 4A




FIG. 4B




FIG. 4C




FIG. 5

**DECLARATION FOR PATENT APPLICATION
AND POWER OF ATTORNEY**

As a below named inventor, I hereby declare that:

My residence, post office address and citizenship are as stated below adjacent to my name.

I believe I am an original, first and joint inventor of subject matter (process, machine, manufacture, or composition of matter, or an improvement thereof) which is claimed and for which a patent is sought by way of the application entitled

**METHOD OF DECRYPTING DATA STORED ON A STORAGE DEVICE USING AN
EMBEDDED ENCRYPTION/DECRYPTION MEANS**

which (check) ☒ is attached hereto.
☐ and is amended by the Preliminary Amendment attached hereto.
☐ was filed on _____ as Application Serial No.
☐ and was amended on ____ (if applicable).

I hereby state that I have reviewed and understand the contents of the above identified specification, including the claims, as amended by any amendment referred to above.

I acknowledge the duty to disclose information, which is material to patentability as defined in Title 37, Code of Federal Regulations, § 1.56.

I hereby claim foreign priority benefits under Title 35, United States Code, § 119(a)-(d) of any foreign application(s) for patent or inventor's certificate or any PCT international application(s) designating at least one country other than the United States of America listed below and have also identified below any foreign application(s) for patent or inventor's certificate or any PCT international application(s) designating at least one country other than the United States of America filed by me on the same subject matter having a filing date before that of the application(s) of which priority is claimed:

Prior Foreign Application(s)			Priority Claimed	
Number	Country	Day/Month/Year Filed	Yes	No
N/A			<input type="checkbox"/>	<input type="checkbox"/>

I hereby claim the benefit under Title 35, United States Code, § 119(e) of any United States provisional application(s) listed below:

Provisional Application Number	Filing Date
N/A	

I hereby claim the benefit under Title 35, United States Code, § 120 of any United States application(s) or PCT international application(s) designating the United States of America listed below and, insofar as the subject matter of each of the claims of this application is not disclosed in the prior application(s) in the manner provided by the first paragraph of Title 35, United States Code, § 112, I acknowledge the duty to disclose information, which is material to patentability as defined in Title 37, Code of Federal Regulations, § 1.56, which became available between the filing date of the prior application(s) and the national or PCT international filing date of this application:

Application Serial No.	Filing Date	Status (patented, pending, abandoned)
N/A		

I hereby appoint the following attorney(s) and/or agent(s) to prosecute this application and to transact all business in the United States Patent and Trademark Office connected therewith:

Alan H. MacPherson (24,423); Brian D. Ogonowsky (31,988); David W. Heid (25,875); Norman R. Klivans (33,003); Edward C. Kwok (33,938); David E. Steuber (25,557); Michael Shenker (34,250); Stephen A. Terrile (32,946); Peter H. Kang (40,350); Ronald J. Meetin (29,089); Ken John Koestner (33,004); Omkar K. Suryadevara (36,320); David T. Millers (37,396); Kent B. Chambers (38,839); Michael P. Adams (34,763); Robert B. Morrill (43,817); Michael J. Halbert (40,633); Gary J. Edwards (41,008); James E. Parsons (34,691); Daniel P. Stewart (41,332); Philip W. Woo (39,880); John T. Winburn (26,822); Tom Chen (42,406); Fabio E. Marino (43,339); William W. Holloway (26,182); Don C. Lawrence (31,975); Marc R. Ascolese (42,268); Carmen C. Cook (42,433); David G. Dolezal (41,711); Roberta P. Saxon (43,087); Mary Jo Bertani (42,321); Dale R. Cook (42,434); Sam G. Campbell (42,381); Matthew J. Brigham (44,047); Hugh H. Matsubayashi (43,779); Patrick D. Benedicto (40,909); T.J. Singh (39,535); Shireen Irani Bacon (40,494); Rory G. Bens (44,028); George Wolken, Jr. (30,441); John A. Odozynski (28,769); Cameron K. Kerrigan (44,826); Kenneth C. Brooks (38,393); Paul E. Lewkowicz (44,870); Theodore P. Lopez (44,881); Mayankumar M. Dixit (44,064); and Eric Stephenson (38,321).

Please address all correspondence and telephone calls to:

David E. Steuber
Attorney for Applicants
SKJERVEN, MORRILL, MacPHERSON, FRANKLIN & FRIEL LLP
25 Metro Drive, Suite 700
San Jose, California 95110-1349

Telephone: 408-453-9200
Facsimile: 408-453-7979

I declare that all statements made herein of my own knowledge are true, all statements made herein on information and belief are believed to be true, and all statements made herein are made with the knowledge that whoever, in any matter within the jurisdiction of the Patent and Trademark Office, knowingly and willfully falsifies, conceals, or covers up by any trick, scheme, or device a material fact, or makes any false, fictitious or fraudulent statements or representations, or makes or uses any false writing or document knowing the same to contain any false, fictitious or fraudulent statement or entry, shall be subject to the penalties including fine or imprisonment or both as set forth under 18 U.S.C. 1001, and that violations of this paragraph may jeopardize the validity of the application or this document, or the validity or enforceability of any patent, trademark registration, or certificate resulting therefrom.

Full name of first inventor:		DANIEL R. ZAHARRIS	
Inventor's Signature:	<i>Daniel R Zaharris</i>	Date:	5-9-2000
Residence:	Longmont, CO		
Post Office Address:	7329 Mt. Meeker Road Longmont, CO	Citizenship:	USA

Full name of second inventor:		LANE W. LEE	
Inventor's Signature:	<i>Lane W Lee</i>	Date:	5-9-2000
Residence:	Lafayette, CO		
Post Office Address:	894 S. Bermont Drive Lafayette, CO 80026	Citizenship:	USA